



## DEVIreg™ 532

The DEVIreg™ 532 is a simple electronic thermostat with a 2-pole switch, using the room sensor to control the room temperature and the floor sensor (wire) to limit the maximum floor temperature. It can be either flush-mounted or surface-mounted.

The thermostat has a dial for adjusting the temperature, with a scale from 5° C - 35° C and an LED indicating the current mode (heating, standby or fault).

### Benefits:

- 2-pole safety breaker
- Sensor failure monitoring
- LED indication
- Room and floor sensors
- Frost protection

### Standard compliance:

- EN/IEC 60730-1 (general) and EN/IEC 60730-2-9 (thermostat)

### Approvals:



Type	Value
Operation voltage	220 V- 240V~ 50/60 Hz
Standby power consumption	max. 0.25 W
Relay:	
Resistive load	Max 15A / 3450W @ 230V
Inductive load	Cos Φ = 0.3 max. 1A
Sensing unit	NTC 15 kOhm at 25° C
Hysteresis	± 0.4° C
Ambient temperature	-10° C. to +30° C
Frost protection	5° C - ❄
Temperature range	5° C -35° C room temperature 20° C -50° C floor temperature limiter - default 35° C
Cable specification max	1 x 4 mm <sup>2</sup> or 2 x 2,5 mm <sup>2</sup>
Ball pressure test temperature	75° C
Pollution degree	2 (domestic use)
Controller type	1 C
Storage temperature	-20° C to +65° C
IP class	31
Protection class	Class II - □
Dimensions (H/W/D)	85 mm x 85 mm x 36 mm
Weight	90 g

### Types

Code No.	Name	Description
01-140F1037	DEVIreg™532	Flush Mounted Manual Floor and Room Air sensing thermostat (Supplied for fitting to a Euro Flush Box)
<b>Accessory</b>		
08-AP	Adapter Plate	Adapter Plate to enable fitting to a Standard NZ Flush Box
08-1547	Euro Box (Metal)	Euro Flush box for wall mounting thermostat as supplied
08-1548	Euro Box (Plastic)	Euro Flush box for wall mounting thermostat as supplied

